DEH-K SERIES · INDUSTRIAL STATIONARY DEHUMIDIFIERS

DanVex DEH-10K

Stationary industrial dehumidifier · 1000 L/day · Full Inverter · 9500–12000 m³/h



Stationary industrial dehumidifiers for permanent installation where humidity control is part of the building or process specification — manufacturing sites, large warehouses and logistics hubs, food and pharmaceutical production, and indoor cultivation.

Vertical top-discharge airflow distributes dry air evenly throughout the room volume and reaches the upper layers where moisture collects, while the inverter compressor and fan modulate output to match the load — cutting running costs in large spaces.

Manufacturing · Large warehouses · Food production · Pharmaceutical · Logistics & distribution · Indoor cultivation

KEY FEATURES

- **Full Inverter system** — matches output to real load; up to 40% energy saving, no humidity spikes
- **Top-discharge airflow** — reaches the upper room volume; connects straight to overhead ducting
- **UV Steriliser + Anion Generator** — reduces airborne bacteria, mould spores and pathogens
- **E-Coating heat exchanger** — anti-corrosion layer; resists acids, brines, chlorinated agents
- **5-in-1 air quality sensor** — CO_2 · PM2.5 · TVOC · RH · T°
- **Wi-Fi + Modbus RTU RS-485** — app control and BMS/SCADA integration on every model


SPECIFICATIONS

Dehumidification	**1000 L/day**
Supply airflow	**9500–12000 m³/h**
External static pressure	**300 Pa**
Operating temperature	**+5 … +38 °C**
Working humidity range	**30–100% RH**
Voltage / Frequency	**380–415 V 3-phase / 50–60 Hz**
Compressor	**Full Inverter, R-32**
Fan system	**Smart-Inverter EC (0–100%)**
Heat exchanger protection	**E-Coating**
Defrost system	**Hot Gas Defrost**
Air quality sensor	**5-in-1 (CO_2/PM2.5/TVOC/RH/T°)**
Air purification	**UV Steriliser + Anion**

Filtration	**G4**
Rated power (variable)	**18500–21130 W**
Current	**28–32 A**
Refrigerant	**R-32 × 5500 g**
Noise level at 1 m	**40–47 dB(A)**
Water protection	**IPX4**
Dimensions (L×W×H)	**1528 × 670 × 2041 mm**
Package size (L×W×H)	**1600 × 740 × 2200 mm**
Net weight	**330 kg**
Gross weight	**392 kg**
Condensate drain connection	**Ø 32 mm**
Connectivity / BMS	**Wi-Fi + Modbus RTU RS-485**

© 2026 **DanVex** · Industrial & Professional Climate Control

DIMENSIONS & VIEWS



Dimensions in mm. side panel with condensate drain and power supply, front view with return-air intake, side view, plan view with top supply-air outlet.

UNIT L×W×H	PACKAGE L×W×H	NET / GROSS WEIGHT	CONDENSATE DRAIN
1528 × 670 × 2041 mm	**1600 × 740 × 2200 mm**	**330 kg / 392 kg**	**Ø 32 mm**

SCOPE OF SUPPLY

- Stationary dehumidifier unit — G4 filter fitted; UV air sanitiser, anion generator, 5-in-1 sensor, Wi-Fi and Modbus RTU RS-485 integrated; factory refrigerant charge (R-32)
- Electronic controller with built-in humidity sensor
- Remote control module

INSTALLATION & CONNECTIONS

Mounting	Floor-standing unit for permanent installation in production halls, warehouses and process areas; place on a level floor with free space in front of the intake grille and above the top outlet.
Air distribution	Top vertical discharge distributes dry air through the upper zone of high rooms and avoids short-circuiting to the intake. The top outlet can be connected to ductwork for distribution to several zones.
Condensate drain	Ø 32 mm drain connection on the side panel; connect to a drain line with continuous fall.
Electrical supply	380–415 V, 3-phase, 50–60 Hz. Dedicated circuit with circuit breaker sized per model current and local code; connection by a certified electrician.
Control & BMS	Electronic controller with built-in humidity sensor or remote control module (both included). Modbus RTU RS-485 for BMS/SCADA; Wi-Fi for app control.
Service	Filter access through the front panel; G4 filter cleaned or replaced per the manual.

DEH-K SERIES — MODEL RANGE

Parameter	DEH-2K	DEH-2K Inverter	DEH-3K	DEH-5K	DEH-10K
Dehumidification	200 L/day	240 L/day	300 L/day	500 L/day	**1000 L/day**
Supply airflow	2500 m³/h	2800–3200 m³/h	2800–3500 m³/h	4800–5300 m³/h	**9500–12000 m³/h**
External static pressure	200 Pa	200 Pa	200 Pa	250 Pa	**300 Pa**
Voltage / Frequency	380–415 V 3-phase / 50–60 Hz	220–230 V 1-phase / 50–60 Hz	380–415 V 3-phase / 50–60 Hz	380–415 V 3-phase / 50–60 Hz	**380–415 V 3-phase / 50–60 Hz**
Compressor	R-32	Full Inverter, R-32	Full Inverter, R-32	Full Inverter, R-32	**Full Inverter, R-32**
Fan system	Step-Control AC (multi-speed)	Smart-Inverter EC (0–100%)	Smart-Inverter EC (0–100%)	Smart-Inverter EC (0–100%)	**Smart-Inverter EC (0–100%)**
Heat exchanger protection	Blue Fin	E-Coating	E-Coating	E-Coating	**E-Coating**
Rated power (variable)	4000 W	3040–4200 W	3260–4930 W	6080–9224 W	**18500–21130 W**

Specifications, dimensions and drawings are subject to change without notice and may differ from the delivered unit; verify critical dimensions against the installation manual before design work. Dehumidification capacity measured at 30 °C / 80% RH.